



Features

- 4th Gen Intel® Core™ i7/i5/i3 / Xeon® processors, up to 3.4GHz
- Advanced LAN Bypass
- 8x PCI-E GbE ports with status LED indicator
- 4x DDR3 DIMM; Max. 32GB
- 1x CF slot, 1x Mini PCI-E, 1x mSATA socket (mSATA compatible) socket
- iAMT 9.0 support

Specifications

CPU	LGA1150 socket for 4th Gen Intel® Core™ i7/i5/i3/ Xeon® processors, up to 3.4GHz
Chipset	Intel® C226 PCH
Memory	4x DDR3 DIMMs up to 1600MHz, Max. 32GB UDIMM (ECC or non-ECC)
Display	Supports VGA via pin header
Ethernet	1x Intel® I217LM GbE PHY w/ iAMT 9.0 support 7x Intel® I210-AT GbE
Bypass	2x segment, LAN 5/6 & 7/8
Expansion	2x PCI-E x8 GF, 1x Mini PCI-E slot (PCIe & SATA signal), 1x Mini PCI-E slot (SATA signal)
IPMI	N/A
Storage	2x SATA III ports 1x CF slot
I/O	3x LED (Power / HDD / Status) 1x Factory default button (GPIO) 1x RJ45 console 2x USB 3.0
Power Input	ATX Power
Dimensions	355 mm x 185 mm (13.98" x 7.28")
Operating Temperature	0°C ~ 60°C (32°F~140°F)
Storage Temperature	-20°C ~ 80°C (-4°F~176°F)
Operating Humidity	10% ~ 90% (non-condensing)
Certification	CE/FCC

Ordering Information

MB968	Networking motherboard with 4th Gen Intel® Xeon® Core™ i7/i5/i3 socket, C226 PCH, 4x DDR3 DIMMs, 8x GbE Port, Barebone without CPU/Cooler/RAM
VGA4	VGA cable
USB2-7	Dual port USB 2.0 cable, 300mm
IP331	1-to-1 PCI-E 8x riser card
IP332	PCI-E 8x adaptor card
IP333	2-to-2 PCI-E 8x riser card